



**Setting**

**Chassis Microphone**

- electret condenser microphone
- DIP-SW1.1 ON \*
- DIP-SW1.2 OFF \*
- dynamic microphone
- DIP-SW1.1 OFF
- DIP-SW1.2 ON

**Cabin Microphone**

- electret condenser microphone
- DIP-SW1.3 OFF \*
- DIP-SW1.4 ON \*
- dynamic microphone
- DIP-SW1.3 ON
- DIP-SW1.4 OFF

**Headset Microphone**

- electret condenser microphone
- DIP-SW2.3 OFF \*
- DIP-SW2.4 ON \*
- dynamic microphone
- DIP-SW2.3 ON \*
- DIP-SW2.4 OFF \*

**Mode**

- duplex
- DIP-SW2.2 ON \*
- simplex
- DIP-SW2.2 OFF
- mute ON
- DIP-SW2.1 OFF
- mute OFF
- DIP-SW2.1 ON \*

**Volume**

- Balance R8
- max.Gain
- Volume Chassis Speaker R13
- 50% (60dB ref. to 1kHz)
- Volume Cabin Speaker R3
- 50% (60dB ref. to 1kHz)
- Volume Headset Speaker R35
- 50% (53dB ref. to 1kHz)

**Sound**

- Bass R6
- 3dB at 100Hz ref. to 1kHz
- Treble R7
- 3dB at 10kHz ref. to 1kHz

\*=default



TITLE  
CarCom 24V  
Kaj Larsen Communication A/S

DOCUMENT NUMBER  
WNO80025

DRAWN  
G.T.

DATE  
02.03.04

Copyright Clarson Apparatebau GmbH ALL RIGHTS RESERVED

Sheet 10f 1